

CASA ADHESIVE, INC.

CASA 309

LAMINATING ADHESIVE

DESCRIPTION:

CASA 309 is a non-flammable, non-toxic, aqueous emulsion adhesive for decorative high pressure laminate countertops.

ADVANTAGES:

- High Solids, Superior Coverage
- Excellent Water Resistance
- Low VOC
- Easy Clean Up
- Fast One Part Adhesive System
- Dyed Blue for Enhanced Visibility

APPLICATION:

Surfaces must be clean and dry. Spray an even coat of adhesive to both surfaces to be bonded. Allow both surfaces to become tacky before bonding, usually 2 to 7 minutes. Tack time varies depending on atmospheric conditions such as temperature and humidity, as well as the amount of adhesive applied. Place both surfaces to be bonded in the exact position desired within 20 minutes of adhesive application. If the two surfaces do not grab immediately when brought into contact they have dried too long. The adhesive may be reactivated by applying another thin coat over each surface. Roll with a 3" or 6" hand roller in all directions. Clean up wet adhesive with CASA Quick Clean #6.

PACKAGING:

- 5 Gallon Pails
- 55 Gallon Fiber Drums
- 275 Gallon Disposable Totes

SHELF LIFE:

One Year from the date of manufacture in unopened container.

Manufacturer's Statement:

The statements and technical information contained in this technical data sheet are based on tests and data which CASA Adhesive, Inc. believes to be reliable, however the occurring and completeness of such statements and technical information is not guaranteed. CASA Adhesive, Inc. makes no warranty, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. User is responsible for determining if the product is fit for a particular purpose and is suitable for user's method of application.

CASA ADHESIVE, INC.

206 Nance Road N.E.
Calhoun, GA 30701

Phone: 888-685-0025

Fax: 888-781-5255

Email: casaadhesive@comcast.net