

CASA ADHESIVE, INC.

CASA 3600 PT ROOFING FELT ADHESIVE

DESCRIPTION:

CASA 3600 PT is a non-flammable, non-toxic, “0” VOC canister adhesive for bonding wide width and standard roofing felts and papers to themselves, or to wood roof decking.

ADVANTAGES:

- No solvent
- Zero VOC
- Water-Based
- Tested and exceeds the requirement of ASTM D 3019
- Provides up to 2500 square feet, per canister
- Ends messy “tar drip” clean up

APPLICATION:

Apply a coat of adhesive to the perimeter of the roof decking and to all seam areas while holding the spraying wand perpendicular to the surface being sprayed. Use a **4001** tip to apply a 6” wide adhesive band. Use a **8002** tip for wider, ice dam adhesive applications. Spray on QuickSeal 3600-PT and roll out roofing paper/felt into the adhesive. QuickSeal 3600-PT allows about 20 minutes of “working time” for repositioning. “Walking down” the roofing paper into the adhesive will strengthen the bond. Clean up wet adhesive and equipment with CASA PT Cleaner or Quick Clean #6.

PACKAGING:

- 38# Pressurized Canister

SHELF LIFE:

Six Months from the date of manufacture in unopened container.

Manufacturer’s Statement:

The statements and technical information contained in this technical data sheet are based on tests and data which CASA Adhesive, Inc. believes to be reliable, however the occurring and completeness of such statements and technical information is not guaranteed. CASA Adhesive, Inc. makes no warranty, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. User is responsible for determining if the product is fit for a particular purpose and is suitable for user’s method of application.

CASA ADHESIVE, INC.

206 Nance Road N.E.
Calhoun, GA 30701

Phone: 888-685-0025

Fax: 888-781-5255

Email: casaadhesive@comcast.net