

CASA 3500-PT

Material Safety Data Sheet

Effective Date: 10-07-98 Revised Date: 02-21-08

1. Product Information:

Trade Name:CASA 3500-PT
 Product Number:3500
 Product Name:Pressure Sensitive Tile Adhesive
 Product Class:Water Emulsion Latex Adhesive
 Manufactured By:CASA Adhesive, Inc. 206 Nance Road NE, Calhoun, GA 30701
 Phone: 1-888-685-0025 Fax: 1-888-781-5255
 24-Hour Emergency: Chemtrec Telephone Number: 1-800-424-9300

2. Hazardous Material Identification System:

Health:1
 Reactivity:0
 Flammability:0

3. Hazardous Ingredient:

Ingredient:No hazardous ingredients.

4. Physical Data:

Boiling Point:212° F
 Vapor Density:Heavier than air.
 Evaporation Rate:Same as water.
 Appearance and Odor:Milky Blue/Latex
 Specific Gravity:1.10
 Volatility/Volume (%):35-37%
 Solubility in Water:Soluble
 VOC:0 grams/liter

5. Fire and Explosion Hazard Data:

Flammable limits:No Flashing
 Flash Point:N/A
 Flammability Classification:OSHANone
DOTNone
 Extinguishing MediaCO₂, Chemical Foam, Water Fog
 Special Fire Fighting Features ...Wear self-contained breathing gear when in confined area.

6. Health Hazard Data:

Threshold Limit ValueNone
 Effects of OverexposureNone

7. Emergency and First Aid Procedure:

Keep out of eyes. Flush with water for 10-15 minutes. If irritation persists, consult a physician. May cause slight irritation of the skin. Wash with soap and water. If swallowed, consult a physician.

8. Reactivity Data:

Conditions to avoidExcessive heat or cold
 StabilityStable
 IncompatibilityNone known
 Hazardous Decomposition ProductsNormal (CO₂, CO)
 Hazardous PolymerizationWill not occur

9. Personal Protection Information:

VentilationLocal ventilation
 Protective GlovesRecommended
 Eye ProtectionRecommended
 Hygienic PracticesWash with soap and water after exposure.
 RespiratoryRecommended in poorly ventilated areas.

10. Special Precautions/Disposal/Spill:

Precautions to be taken in handling and storing: Store inside at a temperature of 60° F to 100° F. **DO NOT ALLOW PRODUCT TO FREEZE.**
 Disposal: Care should be taken to ensure that material or its containers are disposed of in approved facility in accordance with federal, state and local regulations.

Spill: Wear appropriate personal protection equipment. Absorb spill with vermiculite or inert material, then place in container for chemical waste.

Caution: Contents under pressure—avoid excessive heat (120° F).

Propellant: UN 1066 2.2 Non-Flammable compressed gas n.o.s.

Other precautions: None

11. Transportation Data:

D.O.T. Hazard Class2.2. Shipments exceeding 1,000 lbs must be placarded. Surface transportation only.

12. Regulatory Information:

TSCA (US Toxic Substance Control Act): All components of this product are listed on the TSCA inventory. Any impurities present in this product are exempt from listing.

DSL (Canadian Domestic Substances List) and **CEPA** (Canadian Environmental Protection Act): All components of this product are listed on the DSL. Any impurities present in this product are exempt from listing.